



PVC & CAUCHO INDUSTRIAL

MANGUERAS Y TUBOS, S.L.

Ctra. De Barcelona, nº183 1er Piso
08290 – CERDANYOLA DEL VALLÈS

BARCELONA (Spain)

Tel: (+34) 93 594 63 11

comercial@soditeccspain.com

www.soditeccspain.com



FICHA TÉCNICA

Tube Vinilo SO-180

Manguera de tela de poliéster con revestimiento de vinilo de PVC cosido de alta resistencia reforzada con un resorte de hélice de alambre de acero y correa de PVC externa.

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
12	.9	N/A	9	10:1	N/A	7
20	1.4	N/A	13	10:1	N/A	3

Technical data based on 2 ft. straight lengths of hose @ 72°

Construction: High strength sewn single-ply PVC vinyl coated polyester fabric hose reinforced with a spring steel wire helix & external PVC wearstrip

Temperature Range: -20°F to 180°F

Standard Color: White with White Wearstrip

Standard Lengths: 25 Feet

- Flame retardant to UL 94V-0

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.